

Sony Mobile Communications
Prepared by
SOMC/CGQBADS Håkan Sjöberg
Contents responsible if other than preparer

Document number
CGQBA13:045
Date
2013-01-18
Remarks

Revision
A

Approved by
SOMC/CGQBADS Håkan Sjöberg

Receiver

Federal Communication Commission and Certification
and Engineering Bureau

Applies to :

| Product | Typenumber | FCC ID |
|---------|------------|------------|
| C6503 | PM-0240-BV | PY7PM-0240 |

Dual Cell HSDPA Declaration Letter

There is no difference between uplink with DC-HSDPA configured and the normal HSDPA case. For the reporting format used on HS-DPCCH for CQI and ACK/NACK reporting please see 3GPP 25.212 4.7.3A.

The RF chain remains unchanged. This implementation described above does not affect uplink modulation, spurious emission, bandwidths and temperature behavior. Output power in DC-HSDPA mode is equal or lower than output power in RMC 12.2kbps mode, as demonstrated in this filing.

Secondary carrier share uplink HS-DPCCH according to document 3GPP TS 25.212 s4.7 with the first carrier. Uplink will be power controlled as normal by one stream of TPC commands received on DL DPCH i.e. E-DPDCH, E-DPCCH, DPDCH, DPCCH and HS-DPCCH will all be power controlled jointly.

Based on this the DC-HSDPA mode has been excluded from the testing performed in the EMC test reports.

Signed



Håkan Sjöberg

Manager - HW Verification
Global Type Approval
Sony Mobile Communications AB